



Surface & Suspended

**Low maintenance, affordable and efficient IP65 alternative to the MIS800.**

- A lumen output of 1869lm
- Colour Temperatures: 3000k - 4000k
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Mountings: Wall/Surface Mounting as standard
- Diffuser: Opal (/OP)
- Sensors: Available with microwave sensor for presence detection or corridor function (/MW/CDR)
- Suitable for BESA fixing
- IP Rating: IP65 as standard
- Dimensions: (Diameter x Depth) Ø350 x 135mm

Product	MIS/PLU Surface LED circular			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/20W 1869lm			
Size Depth	Ø350mm 135mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MIS PLUTO LED, 20W, 4000k, 1869lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/PLU/20W/1869lm/DALI/840/WH/OP				

