



**A suspended luminaire for open area spaces. The POLO has a variety of lumen outputs and sizes providing an excellent source of illumination.**

- A range of lumen outputs from 5460-12012lm
- Colour Temperatures: 3000k - 4000k - TWH
- Colours: White or Silver, other colours available (/WH/SLV)
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available in Remote Emergency (/RME3/RME3-ST /RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Distribution: Direct or Direct/Indirect (/DL/UDL)
- Mounting: Suspended as standard (/WS)
- Dimensions: (Diameter x Height)
  - Ø500mm x 80mm
  - Ø700mm x 80mm
  - Ø900mm x 80mm
  - Ø1200mm x 80mm
  - Ø1500mm x 80mm

Product	MIS/POLO Circular LED Suspended					
Light Source	LED					
System Power Luminaire lumens (4000K)	/53W *5460lm	/73W *7644lm	/73W *7644lm	/98W *12012lm		
Size	/500 Ø500mm	/700 Ø700mm	/900 Ø900mm	/1200 Ø1200mm	/1500 Ø1500mm	
Driver	/STD Non-Dimming		/DALI DALI Dimming		/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		/TWH Tunable White	
Colour	/WH White					
Diffuser Options	/OP Opal					
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency		/RME3-WI Remote Three hour Wireless addressable emergency	
To Specify: POLO HUB LED, 73W, 7644lm, 4000k, LED suspended finished white supplied complete with standard control gear. Part code: MIS/POLO/73W/7644lm/STD/840/WH/OP/WS						
*Please note: Wattage and Lumen figures are based from Indirect/Direct version.						

