



The POWERPACK is an IP66 decorative and robust wall mounted amenity luminaire. Suitable for mounting heights 4-8m. Finished powder coated black.

- A range of lumen outputs from 2140-4454lm
- Colour Temperature: 3000k - 4000k - 5000k
- Lens: Clear one piece moulded lens.
- Colours: Black RAL9005 Finish (/BK)
- Available with Dimming (/STD/1-10V/SDIM)
- Emergency Options(/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Distribution: Asymmetric (/ASY)
- Mounting: Wall mounted
- Sensor: Photocell or Microwave Sensor (/PC/MW)
- IP Rating: IP66
- Housing: Die cast aluminium
- Dimensions: (Length x Width x Depth)
280 x 220 x 146mm

Product	MI/POWERP Wall IP66 LED Luminaire			
Light Source	LED			
System Power <small>Luminaire lumens (4000K)</small>	/19.4W 2140lm	/28.4W 3147lm	/41.8W 4454lm	
Size	280 x 220 x 146mm			
Driver	/STD Non Dimming	/1-10V 1-10V dimming	/SDIM Switch dimming	
Colour Temperature	/830 3000k	/840 4000k	/850 5000k	
Colour	/BK Black RAL9005			
Optic Distribution	/ASY Asymmetric			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: Powerpack, 19.4W, 2140lm, 4000k, LED wall mounted luminaire with Asymmetric distribution, finished black complete with standard integral control gear. Part code: MI/PowerP/19.4W/2140lm/STD/840/ASY/BK				

