



The STEP LED is suitable for both surface-mounted and recessed installation. Can be installed flush with the wall using an optional back box accessory. Designed for minimal wall thickness requirements.

- A range lumen outputs from 1077 or 2345lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Colour: Dark Grey, Light Grey or Bronze (/DGR/LGR/BR)
- Available with dimming (/STD/MDIM)
- Emergency not available
- Mounting: Surface, Recessed or Flushed (/SM/R/FL)
- IP Rating: IP65
- Housing: Low copper content die-cast aluminium
- Dimensions: (Length x Width x Depth)
/SQ - 175 x 175 x 30 mm
/RECT - 280 x 150 x 31 mm

Product	MI/STEP IP65 STEP Light LED Luminaire		
Light Source	LED		
System Power Luminaire lumens (5000K)	/8W 1077lm	/16W 2345lm	
Size (Length x Width x Depth)	/SQ 175 x 175 x 30 mm	/RECT 280 x 150 x 31 mm	
Driver	/STD Non Dimming		/MDIM Mains Dimming
Colour Temperature	/827 2700k	/830 3000k	/840 4000k
Colour	/DGR Dark Grey	/LGR Light Grey	/BR Bronze
Mounting	/SM Surface Mounted	/R Recessed	/FL Recessed Flushed
Emergency	n/a		
To Specify: Square Step LED, 8W, 1077lm, 4000k, LED surface mounted finished dark grey complete with standard control gear. Part code: MI/STEP/SQ/8W/1077lm/STD/840/DGR/SM			

Rectangle Version (/RECT)

