TITAN HS





Titan Highly Specular

A high quality, cost effective LED downlight with a shallow profile and IP65 rating. The E4 & E6 (830/840) are stock options. Other options available to order.

- A range of lumen outputs from 1300-5400lm
- Colour Temperatures: 3000k 4000k
- Colour: White (/WH)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)

- Reflector Options: Highly Specular with 40° beam angle
- IP Rating: IP65
- Cut-Out Dimensions: (Diameter) -See Table Below
- Depth: E4 80mm (15W + 21W)
- Depth: E6 92mm (21W + 28W)
- Depth: E8 102mm (21W + 28W + 56W)

Product	MID/TTN/HS Recessed TITAN Downlight										
Light Source	LED										
System Power Luminaire lumens (4000K)	/15W 1300lm	, –	/21W 1800lm			/28W 2800lm			/56W 5400lm		
Size _{Cutout}	E4 - 147mm E4 - 125mm				E6 - 208mm E6 - 175mm			E8 - 230mm E8 - 205mm			
Driver	/STD Non Dimming	D	/DALI ALI Dimming	Swi	/SDIM Switch Dimming		Mai	/MDIM Mains Dimming		/WI Wireless Control	
Colour Temperature	/830 3000k				/840 4000k						
Bezel Colour	/WH White										
Reflector Options	/HS Highly Specular										
Emergency	/ME3 Three hour mainta emergency		/ME3-ST Three hour maintained self test emergency		/ME3-PRO Three hour DALI addressable emergency		/ME3-WI Three hour wireless addressable emergency				
To Specify: TITAN E6 LED, Control Gear. Part code: N					ıppli	ed with an	highly s	pecular re	eflector	and Standard	

