



Titan Opal

**A high quality, cost effective LED downlight with a shallow profile and IP65 rating. The E4 & E6 (830/840) are stock options. Other options available to order.**

- A range of lumen outputs from 1300-3700lm
- Colour Temperatures: 3000k - 4000k
- Colour: White (/WH)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Reflector Options: Opal with 80° beam angle
- IP Rating: IP65
- Cut-Out Dimensions: (Diameter) - See Table Below
- Depth: E4 - 80mm
- Depth: E6 - 92mm
- Depth: E8 - 102mm

Product	MID/TTN/OP Recessed TITAN Downlight				
Light Source	LED				
System Power <small>Luminaire lumens (4000K)</small>	/16W 1300lm	/22W 2200lm	/40W 3700lm		
Size Cut-out	<b>E4 - 147mm</b> E4 - 127mm		<b>E6 - 208mm</b> E6 - 175mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Bezel Colour	/WH White				
Reflector Options	/OP Opal				
Emergency	/ME3 Three hour maintained emergency	/ME3-ST Three hour maintained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour wireless addressable emergency	
To Specify: TITAN E6 LED, 22W, 2200lm, 4000k, LED downlight finished white supplied with an opal reflector and Standard Control Gear. Part code: MID/TTN/E6/22W/2200lm/STD/840/WH/OP					

