

TRK-4CELL



The Cell range includes 4-cell and 7-cell linear fittings, available for track, surface, or recessed mounting. Its compact and distinctive design delivers both versatility and a sleek, contemporary aesthetic.

- A range of lumen outputs from 542-1084lm
- Colour Temperatures: 3000K - 4000K
- Beam Angles: (/50D/80D)
- Colours: Black or White (/BK/WH)
- Available with Dimming (/STD/DALI)
- Refer to track system page **84** for the following mountings, Recessed and Wire suspended
- CRI80 as standard, CRI90 available
- Dimensions: (Length x Width x Height)
165 x 50 x 85mm

Product	MI/TRK-4CELL LED Linear Lamp Suited For Track			
Light Source	LED			
System Power Luminaire lumens (4000K)	/4.1W 542lm	/5.5W 723m	/6.9W 904m	/8.3W 1084lm
Size	165 x 50 x 85mm (Length x Width x Height)			
Driver	/STD Non Dimming		/DALI DALI Dimming	
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White RAL9016		/BK Black RAL9005	
Beam Angle	/50D 50 Degrees		/80D 50 Degrees	
Emergency	Remote EMLED TRK available			
To Specify: MI/TRK/4CELL 8.3W, 4000k, 1084lm, 50 degree beam angle, LED surface mounted linear spotlight supplied with DALI control gear and finished in black. Part code: MI/TRK/4CELL 8.3W/1084lm/DALI/840/BK/50D				

Recessed Veriosn
MIR/4CELL



Surface Mounted
Veriosn MIS/4CELL

