



Surface & Suspended

**An elegant and sophisticated LED luminaire. Ideal for meeting rooms and reception areas where there is a high ceiling.**

- A range of lumen outputs from 3542-8316lm
- Colour Temperatures: 3000k - 4000k
- Colours: White or Silver, other colours available (/WH/SLV)
- Available with Dimming (/STD/DALI/SDIM)
- Wireless Control (/WI)
- Available in Remote Emergency (/RME3/RME3-ST /RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Mounting: Wire suspended as standard, Surface mounted available (/WS/SM)
- Recessing kit available. Please contact technical for further details
- Dimensions: (Diameter x Height)
  - /500 - Ø500 x 115mm
  - /700 - Ø700 x 115mm
  - /900 - Ø900x 115mm

Product	MIS/UFO Suspended LED Pendant			
Light Source	LED			
System Power Luminaire lumens (4000K)	/33W 3542lm	/58W 6352lm	/77W 8316lm	
Size	/500 Ø500mm	/700 Ø700mm	/900 Ø900mm	
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k	
Colour	/WH White		/SLV Silver	
Diffuser Options	/OP Opal			
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote Three hour Wireless addressable emergency
To Specify: UFO LED, 77W, 8316lm, 4000k, LED suspended finished white supplied complete with standard control gear and wire suspension kit. Part code: MIS/UFO/77W/8316lm/900mm/STD/840/WH/OP/WS				

