V-ILS ENGINE



Black Reflector
/BKR

Honey Comb attachment
/HC

Gold Reflector
/GDR

The V-ILS engines are highly efficient with its compact design and a wide range of bezels to tailor to your desired finish.

- A lumen output of 950lm or 1429lm
- Colour Temperatures: 2700K - 3000K - 4000K
- Beam Lens: 15°, 25°, 35° or 60° (/15D/25D/35D/60D)
- Available with Dimming (/STD/1-10V/DALI/MDIM)
- Wireless Control (/WI) & Wireless Emergency (/RME3-WI)
- Remote Emergency: (/RME3/RME3-ST/RME3-PRO)
- Reflectors Colours: Black or Gold (/BKR/GDR)
- IP Rating: IP44
- CRI80 as standard, CRI90 Available
- Made from aluminium and electroplating
- Dimensions: (Diameter x Height x Width)
  Ø50 x 65 x 63mm
- Honey comb attachment available (/HC)
- For Full Range of attachements **see pages 8-9**

Product	MID/V-ILS V-ILS Engine				
Light Source	LED				
System Power Luminaire lumens (4000k)	/10.6W 1016lm	/14.8W 1429lm			
Size	Ø50 x 65 x 63mm				
Driver	/STD Non Dimming	/1-10V 1-10V Dimming	/DALI DALI Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/827 2700K	/830 3000K	/840 4000K		
Reflector Colours	/BKR Black Reflector	/GDR Gold Reflector			
Beam Angle	/15D 15 Degrees	/25D 25 Degrees	/35D 35 Degrees	/60D 60 Degrees	
Emergency	/RME3 Remote three hour maintained emergency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three DALI addressable emergency	/RME3-WI Remote three hour wireless addressable emergency	

To Specify: V-ILS, D5, 10.6W, 1016lm, 4000K, LED downlight with 15 degree narrow beam lens and DALI control gear, finished with a gold reflector. Part code: MID/V-ILS/D5/10.6W/1016lm/DALI/840/15D/GDR

Side Profile View
Dimensions





01268 725086 | www.midlighting.co.uk | sales@midlighting.co.uk

Due to ongoing research and development specifications are subject to change without prior notice. Some availability subject to minimum order. All luminaire lumens are 4000k colour temperature readings.

29