




Surface & Suspended

Low maintenance, affordable and efficient IP44 LED bulkhead luminaire. Designed with a unique replaceable gear tray and integral sensor options.

- A range of lumen outputs of 1500lm or 3000lm
- Colour Temperature: 4000k
- Available with Dimming (/STD/DALI)
- Wireless Control (/WI)
- Available with Emergency (/ME3/ME3-ST/ME3-PRO)
- Wireless Emergency (/ME3-WI)
- Diffuser: Opal (/OP)
- Mountings: Wall/Surface Mounting as standard
- Sensors: Available with microwave sensor for presence detection or corridor function (/MW/CDR)
- IP Rating: IP44 as standard
- Dimensions: (Diameter X Depth)
Ø400 x 107mm

Product	MIS/VENUS Surface LED circular			
Light Source	LED			
System Power	/22W 1500lm			/42W 3000lm
Size Depth	Ø400mm 107mm			
Driver	/STD Non Dimming	/DALI DALI Dimming	/WI Wireless Control	
Colour Temperature	/840 4000k			
Colour	/WH White			
Diffuser Options	/OP Opal Diffuser			
Emergency	/ME3 Three hour main- tained emergency	/ME3-ST Three hour main- tained self test emergency	/ME3-PRO Three hour DALI addressable emergency	/ME3-WI Three hour Wireless addressable emergency
To Specify: MIS VENUS LED, 22W, 4000k, 1500lm LED surface circular finished white supplied complete with DALI control gear and opal diffuser. Part code: MIS/VENUS/22W/1500lm/DALI/840/WH/OP				

Unique Hinged gear tray



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
-------	--------------------	---------	--------	------	--------	--------------------	---------	-----------