


WAFER-L RECESSED



An architectural, recessed, linear ultra shallow LED solution. Recessed; ideal for restricted ceiling heights and voids.

- A lumen output of 1371lm or 2386lm
- Colour Temperatures: 3000k - 4000k
- Colours: White (/WH)
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with remote Emergency (/RME3/RME3-ST /RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Diffuser: Opal (/OP)
- Dimensions: (Length x Width x Depth without driver)
 - /20W - 600 x 150 x 22mm
 - /40W - 1200 x 150 x 22mm
- Shallow Depth: 22mm (depth without driver, driver depth may vary)

Product	MIR/WAF-L Recessed WAFER Linear				
Light Source	LED				
System Power Luminaire lumens (4000K)	/20W 1371lm		/40W 2386lm		
Size Cut-out	/6 600mm 582mm x 132mm		/12 1200mm 1182mm x 132mm		
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming	/WI Wireless Control
Colour Temperature	/830 3000k		/840 4000k		
Bezel Colour	/WH White				
Diffuser Options	/OP Opal Diffuser				
Emergency	/RME3 Remote three hour maintained emer- gency	/RME3-ST Remote three hour maintained self test emergency	/RME3-PRO Remote three hour DALI addressable emergency	/RME3-WI Remote three hour Wireless addressable emergency	
To Specify: WAFER-L LED, 40W, 4000k, 2386lm LED recessed luminaire finished white complete with remote control gear. Part code: MIR/WAF-L/40W/2386lm/12/STD/840/WH/OP					



MIR/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style	Range abbreviation	Wattage	Lumens	Size	Driver	Colour Temperature	Options	Emergency
-------	--------------------	---------	--------	------	--------	--------------------	---------	-----------