



ILS 6W

ILS 9W


LS 13W & 18W

A competitive, interchangeable and architectural LED downlight system.

An alternative light engine to a MR16 or GU10 lamp.

- A range of lumen outputs from 650lm to 1800lm
- Colour Temperatures: 2700k - 3000k - 4000k
- Beam Angles: 22°/ 36°/ 60°
- Colours: Polished Aluminium finish as standard
- Available with Dimming (/STD/DALI/SDIM/MDIM)
- Wireless Control (/WI)
- Available with Emergency (/RME3/RME3-ST/RME3-PRO)
- Wireless Emergency (/RME3-WI)
- Materials: Aluminium Housing, Polycarbonate reflector with aluminium coating

Product	MID/ILS Recessed ILS Downlight			
Lamp	LED			
Lamp Power Luminaire lumens (4000K)	/6W 650lm	/9W 905lm	/13W 1100lm	/18W 1800lm
Driver	/STD Non Dimming	/DALI DALI Dimming	/SDIM Switch Dimming	/MDIM Mains Dimming
Colour Temperature	/827 2700k	/830 3000k		/840 4000k
Colour	Polished Aluminium			
Beam Angle Options	/22D 22 Degree	/36D 36 Degree		/60D 60 Degree
Emergency	/RME3 Remote Three hour maintained emergency	/RME3-ST Remote Three hour maintained self test emergency	/RME3-PRO Remote Three hour DALI addressable emergency	/RME3-WI Remote Three hour wireless addressable emergency
To Specify: MID ILS 9W, 60 degree beam angle, 4000k, 905lm LED downlight, with an ILS bezel attachment; F4 in white. Part code: MID/ILS/9W/905lm/905lm/60D/840/F4/WH* See page 5 for attachment part codes.*				



MID/RANGE/SW/LM/SIZE/DIM/840/OPT/ME3

How to Specify

Style
Range abbreviation
Wattage
Lumens
Size
Driver
Colour Temperature
Options
Emergency

